


## 1CEPX – Metric female swivel 24° with O-ring

### 45° elbow – Light series – Metric swivel nut – ISO 12151-2

**MATERIAL** Galvanised steel with transparent Cr(VI)-free plating.  
Other materials available on request.




| Part No.<br># | DN size |      |             |               | Connection type |    | A<br>mm | B<br>mm | E<br>mm | J<br>mm | Max.<br>WP<br>MPa |
|---------------|---------|------|-------------|---------------|-----------------|----|---------|---------|---------|---------|-------------------|
|               | mm      | inch | Thread size | Tube OD<br>mm |                 |    |         |         |         |         |                   |
| 1CEPX-6-03    | 5       | -03  | 4.8         | 3/16          | M12x1.5         | 6  | 58      | 32      | 17      | 14      | 31.5              |
| 1CEPX-6-04    | 6       | -04  | 6.4         | 1/4           | M12x1.5         | 6  | 72      | 43      | 23      | 17      | 31.5              |
| 1CEPX-8-04    | 6       | -04  | 6.4         | 1/4           | M14x1.5         | 8  | 72      | 43      | 23      | 17      | 42.5              |
| 1CEPX-10-05   | 8       | -05  | 7.9         | 5/16          | M16x1.5         | 10 | 72      | 43      | 20      | 19      | 40.0              |
| 1CEPX-10-06   | 10      | -06  | 9.5         | 3/8           | M16x1.5         | 10 | 70      | 40      | 18      | 19      | 40.0              |
| 1CEPX-12-06   | 10      | -06  | 9.5         | 3/8           | M18x1.5         | 12 | 70      | 40      | 18      | 22      | 35.0              |
| 1CEPX-15-08   | 12      | -08  | 12.7        | 1/2           | M22x1.5         | 15 | 83      | 51      | 21      | 27      | 31.5              |
| 1CEPX-18-10   | 16      | -10  | 15.9        | 5/8           | M26x1.5         | 18 | 96      | 65      | 27      | 32      | 31.5              |
| 1CEPX-22-12   | 20      | -12  | 19.0        | 3/4           | M30x2           | 22 | 114     | 79      | 32      | 36      | 28.0              |
| 1CEPX-28-16   | 25      | -16  | 25.4        | 1             | M36x2           | 28 | 112     | 77      | 35      | 41      | 21.0              |

## 10CPX – Metric female swivel 24° with O-ring

### 45° elbow – Heavy series – Metric swivel nut – ISO 12151-2

**MATERIAL** Galvanised steel with transparent Cr(VI)-free plating.  
Other materials available on request.



| Part No.<br># | DN size |      |             |               | Connection type |    | A<br>mm | B<br>mm | E<br>mm | J<br>mm | Max.<br>WP<br>MPa |
|---------------|---------|------|-------------|---------------|-----------------|----|---------|---------|---------|---------|-------------------|
|               | mm      | inch | Thread size | Tube OD<br>mm |                 |    |         |         |         |         |                   |
| 10CPX-8-03    | 5       | -03  | 4.8         | 3/16          | M16x1.5         | 8  | 61      | 35      | 20      | 19      | 63.0              |
| 10CPX-10-04   | 6       | -04  | 6.4         | 1/4           | M18x1.5         | 10 | 74      | 45      | 24      | 22      | 63.0              |
| 10CPX-12-05   | 8       | -05  | 7.9         | 5/16          | M20x1.5         | 12 | 71      | 42      | 20      | 24      | 63.0              |
| 10CPX-14-06   | 10      | -06  | 9.5         | 3/8           | M22x1.5         | 14 | 70      | 40      | 19      | 27      | 63.0              |
| 10CPX-16-08   | 12      | -08  | 12.7        | 1/2           | M24x1.5         | 16 | 85      | 53      | 23      | 30      | 42.0              |
| 10CPX-20-10   | 16      | -10  | 15.9        | 5/8           | M30x2           | 20 | 99      | 68      | 29      | 36      | 42.0              |