

# Indicators Series

## Ordering Information

### Product configurator

Box 1	Box 2	Box 3	Box 4	Box 5	Box 6	Box 7	Box 8
<b>FMU</b>	<b>M3</b>	<b>K</b>	<b>V</b>	<b>M</b>	<b>U14</b>	<b>H</b>	

#### Box 1

Code	
Indicator series	Code
Filter monitoring unit	<b>FMU</b>

#### Box 2

Filter type	
Differential pressure indicator	Code
Visual manual reset	M1*
Visual autoreset	<b>M3</b>
Electrical	<b>T1</b>
Electronic 4 LED, PNP, N.O.	<b>F1</b>
Electronic 4 LED, NPN, N.O.	<b>F2</b>
Electronic 4 LED, PNP, N.C.	F3
Electronic 4 LED, NPN, N.C.	F4
Programmable with memory logs	L1
Ex version	X1

\* available only with U12 thread

#### Box 3

Indicator setting		
Indicator setting	Standard	Code
1.0 bar (14 psi)	c	<b>F</b>
1.2 bar (17 psi)	a	<b>G</b>
1.5 bar (21 psi)	c	<b>H</b>
2.5 bar (35 psi)	a, b, c	<b>K</b>
5.0 bar (70 psi)	b	<b>M</b>
7.0 bar (98 psi)	c	<b>N</b>
8.5 bar (125 psi)		P

Standard settings:  
a: U14M, former -W3  
b: U14H, former -W6  
c: U12H, former -F6

#### Box 4

Seal type	
Seal material	Code
Nitrile	B
Fluoroelastomer	<b>V</b>
EPDM	E
Neopren	N

#### Box 5

Indicator body	
Indicator body	Code
Aluminium (Box 7, code M)	<b>A</b>
Brass (Box 7, code H)	<b>M</b>
Stainless steel	R

#### Box 6

Thread connection	
Thread connection	Code
3/4" - 16UNF-2A	<b>U12</b>
7/8" - 14UNF-2A	<b>U14</b>

#### Box 7

Max Pressure	
Max pressure	Code
Medium pressure housings (<250 bar)	<b>M</b>
High pressure housings (<420 bar)	<b>H</b>

#### Box 8

Options	
Options	Code
Standard	<b>omit</b>
Other options	factory supplied

Note: F and L type indicators. Non-standard thermal lockout settings shown here.

### Indicator type X1: ATEX $\Delta p$ -indicator

Electronic indicator accordant with ATEX 94/9/EC directive: (Ex) II 2 GD Eex mII T6.  
Degree of protection IP66. For details contact Parker Filtration.

### Connection cable + software for programmable indicator L1

Connection cable for PC serial connection and software for indicator settings and utilising memory logs.

**Ordering Code: 905075030**

### Seal kits (fluoroelastomer)

Indicators with thread connection U12H (former -F6)  
Indicators with thread connection U14M (former -W3)  
Indicators with thread connection U14H (former -W6)

### Ordering code

**911045078**  
**911045086**  
**911045087**

Note 1: Part numbers featured with bold highlighted codes will ensure a 'standard' product selection.  
Note 2: Alternate displayed part number selection will require you to contact Parker Filtration for availability.