


ISO C

**Technical Data****max. Working Pressure** 12 bar**Temperature Range** -20°C up to +100°C (NBR)**Flow rate** 810 l/min.
At input pressure 6 bar, pressure drop 0.6 bar**Material**
Coupling: Anodised Aluminium, Nickel plated brass
Plug: Nickel plated steel
Seal: NBR**Coupler - Male Thread**

C	Part Number
G 1/4	18KPAW13APX
G 3/8	18KPAW17APX
G 1/2	18KPAW21APX

Plug - Male Thread


C	Part Number
G 1/4	18SFAW13SXN
G 3/8	18SFAW17SXN

Coupler - Female Thread

C	Part Number
G 1/4	18KPIW13APX
G 3/8	18KPIW17APX
G 1/2	18KPIW21APX

Plug - Female Thread

C	Part Number
G 1/4	18SFIW13SXN
G 3/8	18SFIW17SXN

Coupler - Hose Barb

I.D. Hose	Part Number
6 mm	18KPTF06APX
8 mm	18KPTF08APX
9 mm	18KPTF09APX
13 mm	18KPTF13APX

Plug - Hose Barb

I.D. Hose	Part Number
6 mm	18SFTF06SXN
8 mm	18SFTF08SXN
10 mm	18SFTF10SXN
13 mm	18SFTF13SXN