

DRINCONN STEEL P.L. FOOD QUALITY



✓ **Ottima mandata ed aspirazione liquidi alimentari.**
Great suction and delivery of food liquids.

✓ **Tubo universale.**
Universal hose.



IMPIEGO / APPLICATIONS

[IT]

Tubo universale in PVC idoneo alla mandata ed ottima aspirazione di liquidi alimentari secondo il Regolamento Europeo n. 10/2011 per simulanti A-B-C. La spirale metallica lo rende estremamente flessibile e la trasparenza permette di vedere il passaggio del liquido.

[EN]

Universal pvc hose suitable for suction and delivery of food liquids according to EU Regulation 10/2011 for A-B-C simulants. The steel wire spiral makes it extremely flexible and the transparency lets see the liquid passage.



STRUTTURA / BODY

| | | |
|----------|--------------------------------|--|
| A | Materiale / Material | PVC flessibile. Strong, very flexible and smooth non-toxic, transparent plasticized PVC. |
| B | Inserti / Reinforcement | Spirale in acciaio annegata nella parete del tubo. Steel wire spiral incorporated in hose wall. |
| C | Copertura / Cover | PVC trasparente. Transparent PVC. |
| | Superficie / Surface | Liscia, trasparente. Smooth, transparent. |

| mm | mm | bar | bar | bar | gr/mt | mm | m |
|-------|-----|-----|-----|------|-------|-----|-------|
| 10 | 3,0 | 7 | - | 0,85 | 160 | 20 | 60/30 |
| 12 | 3,0 | 7 | - | 0,85 | 180 | 25 | 60/30 |
| 13 | 3,0 | 6 | - | 0,85 | 190 | 27 | 60/30 |
| 14 | 3,0 | 6 | - | 0,85 | 200 | 30 | 60/30 |
| 16 | 3,1 | 6 | - | 0,85 | 225 | 35 | 60/30 |
| 18 | 3,1 | 6 | - | 0,85 | 280 | 40 | 60/30 |
| 19 | 3,1 | 5 | - | 0,85 | 310 | 42 | 60/30 |
| 20 | 3,1 | 5 | - | 0,85 | 340 | 50 | 60/30 |
| 22 | 3,2 | 5 | - | 0,85 | 370 | 55 | 60/30 |
| 25 | 3,2 | 5 | - | 0,85 | 510 | 60 | 60/30 |
| 30 | 3,5 | 4 | - | 0,85 | 600 | 70 | 60/30 |
| 32 | 3,9 | 4 | - | 0,85 | 650 | 75 | 30 |
| 35 | 4,2 | 4 | - | 0,85 | 730 | 80 | 30 |
| 38 | 4,4 | 4 | - | 0,85 | 800 | 90 | 30 |
| 40 | 4,5 | 3 | - | 0,85 | 870 | 95 | 30 |
| 45 | 5,1 | 3 | - | 0,8 | 1100 | 105 | 30 |
| 50/51 | 5,1 | 3 | - | 0,8 | 1200 | 125 | 30 |
| 60 | 6,5 | 2,5 | - | 0,7 | 1800 | 135 | 30 |
| 63 | 6,5 | 2,5 | - | 0,7 | 1950 | 150 | 30 |
| 63 | 6,5 | 2,5 | - | 0,7 | 2000 | 140 | 30 |
| 70 | 7 | 2 | - | 0,7 | 2200 | 180 | 30 |
| 75 | 7 | 2 | - | 0,7 | 2500 | 195 | 30 |
| 80 | 7,5 | 2 | - | 0,7 | 2700 | 220 | 30 |
| 90 | 7,5 | 2 | - | 0,6 | 3000 | 260 | 30 |
| 102 | 8 | 2 | - | 0,6 | 3400 | 300 | 30 |



FASCETTE E COLLARI STRINGITUBO CONSIGLIATE RECOMMENDED CLAMP/COLLAR

STF - Fascette a vite / Hose clamps with screw

STC - Fascette con bullone / Hose clamps with bolt



NORME / NORMS:
REG. UE 10/2011 FOR SIMULANT TYPE A-B-C
ISO 1307



-5°C / +60°C
+23°F / +140°F