

# ABRACONN FLOSTER EPDM HD



✓ Copertura particolarmente resistente ad agenti atmosferici.  
*Wear resistant cover.*



## IMPIEGO / APPLICATIONS

[IT]

Utilizzata comunemente come rivestimento di tamburi metallici nel settore dei nastri trasportatori, o come protezione di superfici metalliche. Particolarmente indicata per offrire una discreta resistenza all'abrasione ed alla lacerazione, discrete caratteristiche fisico meccaniche.

[EN]

Commonly used as a coating on metal drums in the conveyor belt sector or to protect metal surfaces. In particular, it is indicated to offer fair resistance against abrasion and laceration. It has fair physical and mechanical characteristics.



## STRUTTURA / BODY

A

### Materiale / Material

Tubo prodotto su mandrino bistrato;  
Sottostrato in gomma naturale (NR)  
copertura in gomma BR/EPDM di colore  
nero.  
Abrasion resistant 2 tone natural rubber  
light brown inside black outside.

C

### Inseriti / Reinforcement

Liscia ad impressione tela.

*Smooth with fabric impression.*

### Superficie / Surface

### Colore / Color

Interno nocciola chiaro, esterno nero

### Durezza / Hardness

45 shore a  $\pm$  5

### Carico di rottura /

### Breaking strenght

150 kg/cm<sup>2</sup>

### Allungamento a rottura /

### Breaking elongation

400%



## FASCETTE E COLLARI STRINGITUBO CONSIGLIATE RECOMMENDED CLAMP/COLLAR

STC - Fascette con bullone / Hose clamps  
with bolt



STOCK	mm	mm	bar	gr/mt	mm	m
---	50 x 58	4	-	0,75	-	12
---	60 x 68	4	-	0,88	-	12
---	70 x 78	4	-	1,02	-	12
---	76 x 84	4	-	1,07	-	12
---	80 x 88	4	-	1,16	-	12
---	90 x 98	4	-	1,27	-	12
---	102 x 110	4	-	1,44	-	12
✓	114 x 122	4	-	1,60	-	12
✓	120 x 128	4	-	1,68	-	12
---	130 x 138	4	-	1,83	-	12
✓	140 x 148	4	-	1,95	-	12
✓	152 x 160	4	-	2,11	-	12
✓	168 x 176	4	-	2,32	-	12
✓	193 x 201	4	-	2,68	-	9
✓	200 x 208	4	-	2,76	-	12
✓	220 x 228	4	-	3,03	-	6
✓	254 x 262	4	-	3,50	-	12
✓	273 x 281	4	-	3,74	-	10
✓	305 x 313	4	-	4,20	-	12
✓	323 x 331	4	-	4,42	-	6
✓	350 x 358	4	-	4,81	-	6
✓	400 x 408	4	-	5,52	-	7
✓	500 x 508	4	-	6,81	-	6
✓	612 x 620	4	-	8,50	-	6

i

NORME / NORMS: ISO 1307  
CONFEZIONAMENTO / BOX: ROTOLI TAGLIATI A  
MISURA/ ROLLS CUT TO SIZE

°C

-40°C / +70°C  
-40°F / +158°F